



F **FLOATING**
eco friendly
floating floor



Top coating for residential
or commercial areas
Design layer
High-density fiberboard
Comfort cork backing
Cork granulate underlayment

Unique design options for cork flooring

| FLOATING | ENZO | PLAZA |
|---|--|---------------------------|
| Dimensions EN 427 | 1200 x 210 x 10,5 mm | 612 x 440 x 10,5 mm |
| Classification EN 16511 | | 23/32 |
| Dimensional Stability EN 434 | | 0.1% |
| Castor chair EN 425 | | no visible change |
| Effect of a furniture leg EN 424 | | no visible change |
| Resistance against impact (big ball) EN 13329, Annex F | | no visible change |
| Microscratch resistance DIN EN 16094 | | MSR-A1 / MSR-B3 |
| Abrasion resistance EN 15468:2013, Annex A (Falling-Sand method) | | 5200 revolutions |
| Residual Indentation EN ISO 24343-1 | | 0.13 mm |
| Fire Resistance DIN EN 13501 | | Cfl -s1 |
| Anti-sliding properties EN 13893 | | DS |
| Anti-slip property DIN 51130:2014 | | R9 |
| Formaldehyde emission EN 717-1 | | E1 |
| Electrostatic behaviour EN 1815 | | Antistatic Floor Covering |
| Thermal Resistance EN 12667:2001 | | 0.0982 M2 k/W |
| Impact Sound Reduction EN 140 | | 17 dB |
| Impact Insulation Class IIC according ASTM E 492-09 / ASTM E 989-89 | | 55 dB |
| Locking strength ISO 24334:2006 | Short side joints 4.8 kN/m Long side joints 4.2 kN/m | |

