



DC **DIRECT CLIC**
 ultra-thin
 floating floor



Acoustic
 Embossed Wearlayer
 Design film
 High-density fiberboard
 Cork granulate underlayment

All the strength & comfort in a ultra-thin floating floor

COLLECTIONS	NATURA				
Dimensions EN 427	1200 x 210 x 6,5 mm				
Squareness EN 427	< 0,3 mm				
Straightness EN 427	< 0,2 mm				
Opening between panels EN 14085	< 0,1 mm				
Residual Indentation EN 433	< 0,16 mm				
Dimension Stability EN 434	< 1,5%				
Fire classification EN 13501-1	Efl				
Formaldehyde emission EN 717-1/2	E1				
Impact Noise Reduction ISO 140-8	14 dB				
Microscratch resistance according to EN16094:2012	MSR-A2				
Anti slip properties DIN 51130	R10				
Abrasion resistance according EN15468:2013 annex a	7500 revolutions				
Locking strenght ISO 24336:2005	Short side joints 3.1kN / m		Short side joints 2.7kN / m		
Castor chair test EN 425	no visible change / damages				
Effect of furniture leg EN 424:2002	no visible change / damages				
Resistance against staining EN 438:2	Acetone: grade 5	Coffee: grade 5	NaOH: grade 5	H2O2: grade 5	Shoe polish: grade 5

