



Embossed Wearlayer
with PU finishing
Design film
Comfort layer
100% waterproof
solid board

Premium design flooring with unique characteristics

COLLECTIONS	LUNGO	LUNGO SENSES	EXTEND OAK SENSES / EXTEND PINE SENSES	ORIGINALS	SUPER MATTE OAK / SUPER MATTE COTTAGE OAK	MOONLIGHT	STONE	METROPOLITAN / TREND	XL SLATE	SIGNATURE SENSES / RUSTIC SENSES
Dimensions EN 427	1800x220x6,6	1800x220x6,6	1500x220x6,6	1205x215x5	1205x215x5	620x445x5	620x445x5	1205x215x4,7	1205x445x5	1205x215x5
Emboss / Surface	Regular Wood Emboss Semi-matte	Registered Wood Emboss Semi-matte	Registered Wood Emboss Semi-matte	Deep Wood Emboss Super-matte	Deep Wood Emboss Super-matte	Regular Stone Emboss Semi-matte	Regular Stone Emboss Semi-matte	Regular Wood Semi-matte	Regular Slate Semi-matte	Registered Wood Semi-matte
Class EN 16511	33	33	33	32	32	33	32	33	32	33
Weight EN 430	8 kg/m ²		7 kg/m ²							
Impact Sound Reduction EN 140	7 dB									
Dimensional Stability EN 434	0.1%									
Effect of a castor chair ISO 4918	25.000 cycles no delamination									
Abrasion Resistance EN 660-2	Group T									
Resistance against impact (big ball) EN 13329	no visible change									
Residual Indentation EN 433	≤ 0.2mm									
Fire Resistance DIN EN 13501	Bfl -s1									
Anti-sliding properties EN13893	Class DS									
Slip Resistance DIN 51130	> R9									
Formaldehyde emission EN 717-1	E1									
Emission Values	In accordance to AgBB									
Content of PCP	Not to declare									
Thermal Resistance EN 12667	0.032 m ² K/W									
Chemical Resistance EN 423	Class 0, Excellent									
Color Fastness ISO 105-B02	Minimum 6									
Wet areas	Approved									
Underfloor heating	Approved 27 C									
Locking strength ISO 24334	short side joints: 2.0 kN/m long side joints 1.32 kN/m									



AUTHENTIC LOOK



LOW VOC



ANTI-SLIPPERY



RESISTANT



PHTHALATE FREE



ANTI-STATIC



OK RADIANT HEATING



SOUND REDUCTION



WARM AND COMFORTABLE



RECYCLABLE



EASY TO INSTALL



WATER PROOF

