



**SOLID BOARD
CLIC**
water proof flooring



Embossed Wearlayer
with PU finishing
Design film
100% waterproof
solid board

**Strong
& reliable floors
for wet areas**

COLLECTION	METROPOLITAN
Dimensions EN 427	1230 x 228 x 5 mm
Impact Sound Reduction ISO 717-2	8 dB
Emboss / Surface	Regular Wood Emboss Semi-matte
Classification EN 16511	42
Weight EN 430	9Kg/m ²
Fire Resistance DIN EN 13501	Bf1-S1
Anti-sliding properties EN13893	DS
Slip Resistance DIN 51130	R10
Formaldehyde emission EN 717-1	Class E1 / A+
Content of PCP CEN/TR 14823	Not to declare
Abrasion Resistance EN 660-2	Group T
Residual indentation EN 433	0.05 mm
Thermal conductivity EN 12667:2001	0.076 W/(m·K)
Thermal resistance EN 12667:2001	0.036 m ² ·K/W
Electrostatic properties EN 1815	<2.0 KV
Castor chair EN 425	yes type W EN12529
Dimensional stability EN 434	≤0.10%
Light fastness ISO 105-B02	level ≥ 6 method A
Floor heating system	suitable / max. 27° C
Locking Strenght ISO 243336:2005	Short side joints: 5.8 kN/m Long side joints : 6.9 kN/m



UNICLIC CE U



OK RADIANT
HEATING



EASY
TO INSTALL



GLUELESS
INSTALLATION



ULTRA THIN



WATER
RESISTANT



RESISTANT

COMPETE
2020

PORTUGAL
2020

UNião Europeia
Fundo Europeu
de Desenvolvimento Regional