



**F** **FLOATING**  
design floating floor



NATURAL SHIELD® water base  
urethane varnish  
Natural cork decor  
High-density fiberboard  
Cork granulate underlayment

# Comfortable living is not a luxury.

COLLECTIONS	EXCLUSIVE	ETHERNAL
Dimensions	900 x 300 x 11 mm	900 x 300 x 10 mm
Weight EN 430		8 Kg/m <sup>2</sup>
Level of use Domestic		23
Level of use Commercial		31
Thickness EN 428		10 mm - 11 mm
Dimensions EN 427		900 x 300 mm
Dimensional Stability EN434		0.1%
Resistance against staining EN 438		Grade 1- 5
Resistance to scratching EN 438-2		4N / Grade 3
Residual Indentation EN ISO 24343-1		0.13 mm
Fire Resistance DIN EN 13501		Cfl -s1
Anti-sliding properties EN13893		DS
Formaldehyde emission EN 717-1		E1
Thermal Resistance EN 12667		0.1 (m <sup>2</sup> K)/W
Impact Sound Reduction EN 140		17 dB - 19dB
Impact Insulation Class IIC according ASTM E 492-09 / ASTM E 989-89		55 dB
<b>Locking strength ISO 24334</b>		
Short side joints		4.8 kN/m
Long side joints		4.2 kN/m



ANTI-SLIPPERY



RESISTANT



EASY TO REPAIR



OK RADIANT HEATING



RECYCABLE



ECO-FRIENDLY



ANTI-ALLERGY



PHTHALATE FREE