



F **FLOATING**
design floating floor



Embossed Wearlayer
with PU finishing
Design film
Comfort layer
High-density fiberboard
Cork granulate underlayment

Premium design flooring with unique characteristics



CLASS 32

AUTHENTIC
LOOK

LOW VOC



RECYCLABLE



COMFORTABLE

ANTI-
SLIPPERY

RESISTANT

PHTHALATE
FREEEASY
TO INSTALL

ANTI-STATIC

OK RADIANT
HEATINGSOUND
REDUCTION

COLLECTIONS	ORIGINALS	TREND	SUPER MATTE OAK / SUPER MATTE COTTAGE OAK	STONE	XL SLATE	ESSENTIALS
Dimensions EN 427	1200x210x10,8	1200x210x9,3	1200x210x10,8 mm	612x440x10,8 mm	1200x440x10,8 mm	1200x210x8,2 mm
Emboss / Surface	Deep Wood Semi-matte	Regular Wood Semi-matte	Deep Wood Semi-matte	Regular Stone Semi-matte	Regular Slate Semi-matte	Regular Wood Semi-matte
Classification EN 16511	32		32	32	32	32
Weight EN 430	11 kg/m ²		11 kg/m ²	11 kg/m ²	11 kg/m ²	10 kg/m ²
Impact Sound Reduction en 140	18 dB		18 dB	18 dB	18 dB	17 dB
Fire Performance EN 13501				Bfl - s1		
Anti-sliding properties EN 13893				Class DS		
Formaldehyde emission EN 717-1				Class E1		
Content of PCP CEN / TR 14823				Not to declare		
Dimensional Stability after exposure to heat EN ISO 23999:2012				-0.1%		
Abrasion Resistance EN 15468, Annex A				2500		
Static Indentation EN ISO 24343				0,04 mm		
Resistance against impact (big ball) EN 13329				No visible change		
Chemical Resistance EN 433				Class 0		
Determination of the effect of a castor chair EN 425				No visible change		
Determination of the effect of a furniture eg EN 424				No visible change		
Microscratch resistance EN 16094				MSR-A2 / MSR-B1		
Resistance against staining according to EN 438-2:2016				Coffee: grade 5 / NaOH: grade 4 / H2O2: grade 5 / Shoe polish: grade 5 / Shoe polish: grade 5		
Locking strenght ISO 24334:2006						
- short side joints				5.8 kN/m		
- long side joints				6.9 kN/m		
Underfloor Heating				Approved 27°C		
Thermal Resistance EN 12524				0,088 m ² /W		
Emissions Value				In conformity with AgBB		



UNICLIC

