



**GD** **GLUE DOWN**  
luxury vinyl tile



Embossed Wearlayer  
with PU finishing

Design film  
Confort layer

## Premium design flooring with unique characteristics



CLASS 32



COLLECTIONS	ORIGINALS / TREND	SUPER MATTE OAK / SUPER MATTE COTTAGE OAK	MOONLIGHT / STONE	XL SLATE	LUNGO / LUNGO SENSES
Dimensions EN 427	1212x222x2 1212x222x1,5	1212x222x2	610x457x2,5 622x452x2	1212x452x2	1828x229x2,5
Emboss / Surface	Regular Wood Emboss Semi-matte	Deep Wood Emboss Super-matte	Regular Stone Emboss Semi-matte	Regular Slate Emboss Semi-matte	Regular Wood Emboss/Registered Semi-matte
Class EN 649	32	32	32/42	32	32
Weight EN 430	3,6 kg/m <sup>2</sup>	3,6 kg/m <sup>2</sup>	3,6 kg/m <sup>2</sup>	3,6 kg/m <sup>2</sup>	3,6 kg/m <sup>2</sup>
Impact Sound Reduction EN 140	4 dB	5 dB	5 dB	5 dB	5 dB
Dimensional Stability en 434			Approved		
Fire Resistance EN 131501			Bfl - S1		
Chemical Resistance EN 423			Class 0 - Good		
Abrasion Wear EN 425			Pass Castor Chair (W) DIN 51133 - Class R9 EN 13893 - Class DS		
Slippery Resistance					
Indentation EN 433			max 0,08mm		
Anti-static Resistance EN 1815			< 2kV		
Toxicity EN 71			Non Toxic		
Resistance to Fading ISO 105 B02			6/8 Good		
AbBB/Dibt low VOC (U-Sign)			Certified		
Thermal Resistance EN 12524			0,036 m <sup>2</sup> K/W		
Underfloor Heating			Approved 27°C		
Thermal Conductivity EN 12667			10.076 w(m-k)		



UNICLIC

