



**F** **FLOATING**  
design floating floor



Embossed Wearlayer  
with PU finishing  
Design film  
Comfort layer  
High-density fiberboard  
Cork granulate underlayment

Premium design flooring  
with unique  
characteristics.

FLOATING	SCANDINAVIAN	METROPOLITAN	ORIGINALS	XL SLATE	EXTEND	LUNGO
Dimensions EN 427	1200 x 210 x 9,3mm	1200 x 210 x 9,3mm	1200 x 210 x 9,5mm	1200 x 440 x 10,8mm	1500 x 220 x 10,8mm	1800 x 220 x 10,8mm
Impact Sound Reduction EN 140	17 dB	17 dB	17 dB	18 dB	18 dB	18 dB
Emboss / Surface	Regular Wood Emboss Semi-matte	Regular Wood Emboss Semi-matte	Deep Wood Emboss Super-matte	Regular Slate Emboss Semi-matte	Registered Emboss Semi-matte	Regular Wood Emboss Semi-matte
Class EN 430	33	33	32	32	33	33
Weight EN 430	10 kg/m <sup>2</sup>	10 kg/m <sup>2</sup>	10.75 kg/m <sup>2</sup>	11 kg/m <sup>2</sup>	11 kg/m <sup>2</sup>	11 kg/m <sup>2</sup>
Dimensional Stability EN 434	0,10%					
Fire Resistance EN 131501	Bfl - S1					
Chemical Resistance EN 423	Class 0 - Good					
Abrasion Wear EN 425	Pass Castor Chair (W)					
Slippery Resistance EN 13893	DS (R9 very secure)					
Indentation EN 433	Max 0,03mm					
Anti-static Resistance EN 1815	< 2kV					
Toxicity EN 71	Non Toxic					
Resistance to Fading ISO 105 B02	6/8 depending on design					
Thermal Resistance EN 12524	0,088 m <sup>2</sup> K/W					
AbBB/Dibt low VOC (U-Sign)	Certified					
Underfloor Heating	Approved 27°C					

