



DIRECT CLIC
ultra-thin
floating floor



Acoustic Embossed
Wearlayer
Design Film
High-density fiberboard
Cork Granulate Underlayment

All the strenght & comfort in a ultra-thin floating floor.

DIRECT CLIC	NATURA			
Dimensions EN 427	1200 X 210 mm			
Thickness EN 428	6,5 mm			
Squareness EN 427	< 0,3 mm			
Straightness EN 427	< 0,2 mm			
Opening between panels EN 14085	< 0,1 mm			
Residual Indentation EN 433	< 0,16 mm			
Dimensional Stability EN 434	< 1,5 %			
Fire classification EN 13501-1	Efl			
Formaldehyde emission EN 717-1/2	E1			
Impact Noise Reduction ISO 140-8	14 dB			
Microscratch resistance according to EN16094:2012	MSR-A2			
Anti slip properties DIN 51130	R10			
Abrasion resistance according EN15468:2013 annex a	7500 revolutions			
Locking strength ISO 24336:2005	Short side joints 3.1kN/m		Long side joints 2.7kN/m	
Castor chair test EN 425	no visible change / damages			
Effect of furniture leg EN 424:2002	no visible change / damages			
Resistance against staining EN438:2	Acetone: grade 5	Coffee: grade 5	NaOH: grade 5	H2O2: grade 5 Shoe polish: grade 5

