



# FLOATING

design floating floor



Embossed Wearlayer  
with PU finishing  
Design film  
Pure PVC backing  
High-density fiberboard  
Cork granulate underlayment

## Premium design flooring with unique characteristics.

FLOATING	ORIGINALS / TREND	SUPER MATTE OAK / SUPER MATTE COTTAGE OAK	MOONLIGHT / STONE	XL SLATE	SIGNATURE SENSES / RUSTIC SENSES	EXTEND OAK SENSES / EXTEND PINE SENSES	LUNGO	LUNGO SENSES
Dimensions EN 427	1200 x 210 x 10,8mm 1200 x 210 x 9,3mm	1200 x 210 x 10,8mm	612 x 440 x 10,8mm	1200 x 440 x 10,8mm	1200 x 210 x 10,8mm	1500 x 220 x 10,8mm	1800 x 220 x 10,8mm	1800 x 220 x 10,8mm
Impact Sound Reduction EN 140	18 dB 15 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB
Emboss / Surface	Regular Wood Emboss Semi-matte	Deep Wood Emboss Super-matte	Regular Stone Emboss Semi-matte	Regular Slate Emboss Semi-matte	Registered Emboss Semi-matte	Registered Emboss Semi-matte	Regular Wood Emboss Semi-matte	Registered Emboss Semi-matte
Class EN 430	32	32	32	33	33	33	33	33
Weight EN 430	11 kg/m <sup>2</sup>	11 kg/m <sup>2</sup>	11 kg/m <sup>2</sup>	11 kg/m <sup>2</sup>	11 kg/m <sup>2</sup>	11 kg/m <sup>2</sup>	11 kg/m <sup>2</sup>	11 kg/m <sup>2</sup>
Dimensional Stability EN 434	0,10%							
Fire Resistance EN 131501	Bfl - S1							
Chemical Resistance EN 423	Class 0 - Good							
Abrasion Wear EN 425	Pass Castor Chair (W)							
Slippery Resistance EN 13893	DS (R9 very secure)							
Indentation EN 433	Max 0,03mm							
Anti-static Resistance EN 1815	< 2kV							
Toxicity EN 71	Non Toxic							
Resistance to Fading ISO 105 B02	6/8 depending on design							
Thermal Resistance EN 12524	0,088 m <sup>2</sup> K/W							
AbBB/Dibt low VOC (U-Sign)	Certified							
Underfloor Heating	Approved 27°C							



AUTHENTIC LOOK



LOW VOC



RESISTANT



COMFORTABLE



ANTI-SLIPPERY



PHTHALATE FREE



EASY TO INSTALL



ANTI-STATIC



OK RADIANT HEATING



SOUND REDUCTION

UNICLIC®  
EU Patent 0843 263 B1 - U.S. Patent n. 6,006,686

